

Pressure-activated, automatic shut-off vacuum assist nozzle for full-service and self-service stations.

- V34IS nozzle shuts off when:
 - the pump shuts off.
 - the gas tank is full.
 - the lever is opened before the pump is turned on.
 - the leak detector has not completed the test cycle.
- Stainless steel reinforced spout bushing keeps spout tip round, and acts as a captive fastener to prevent tip-end sensor damage.
- Nozzle is equipped with a unique Flo-Stop® devicet hat shuts off the nozzle if it falls from the fill neck or raises above the horizontal,
- StreamShaper® reduces turbulence for straighter fuel flow and less splash back spillage.
- Tilt poppet design provides precise "to-the-penny" dispensing.

- Strong vapor valve in the nozzle that is mechanically operated by the on-off action of the nozzle's lever.
- Husky® vapor return line is an internal part of the body casting, thus eliminating potential vapor leak points and fugitive evaporative emissions from the fuel remaining in the vapor path of the hose.
- Vapor assist achieved at the body end of the spout where a vapor ring catches emissions.
- Uses international spout and aluminum vapor collector.

MODEL NO. 1357904A*

- ADA-compliant EZ Lever reduces the force required to open the main poppet valve by 50%, resulting in a lever operating force ≤5 lbs.
- Nozzle comes standard with a full grip guard.
- Optional cold weather seals are rated to -40°F/C.
- Optional Gilbarco, Tokheim, and Wayne handguards can be fitted with a magnet to trigger the dispenser's proximity switch, or can be provided without the magnet for dispensers equipped with a standard "flapper" switch.
- Optional vapor insert increases the vapor back pressure, closely matching that of the competition, and making installation a breeze, with little-to-no changes to the vacuum pump draw.
- Optional sightglass provides a clear window for the customer to view the fuel as it passes through the main poppet valve.



MODEL NO.	DESCRIPTION SHIPPING WEI	GHT LBS (KG)	
1357904A*	with Two Notch Hold Open Clip and Aluminum Vapor Collector	3.3 (1.5)	
1357904N^	with Two Notch Hold Open Clip and Aluminum Vapor Collector	3.3 (1.5)	
13748021N^	with Two Notch Hold Open Clip, Overmolded Poppet, Tokheim Magnetic Handguard and Aluminum Vapor Collector	3.3 (1.5)	
14278021N^	with Two Notch Hold Open Clip, Overmolded Poppet, Tokheim Polymer Handguard and Aluminum Vapor	3.3 (1.5)	
E13177041N^	with Two Notch Hold Open Clip, Gilbarco Magnet Handguard, Mate Guard, Polymer Handle Cover and Aluminum Vapor Collector	ic 3.3 (1.5)	
E13986223N^	with Two Notch Hold Open Clip, Wayne Magnetic		
	Handguard, Mate Guard, Polymer Handle Cover and Aluminum Vapor Collector	3.3 (1.5)	
		^ NOT LISTED	















Rev 0 5/24 189




Pressure-activated, automatic shut-off vacuum assist nozzle for full-service and self-service stations.




Construction

One piece sand cast aluminum with high-impact polymer handguard			
Fluorocarbon			
Double o-ring seal protected by fiber-reinforced Teflon®			
Two piece polymer EZ Lever			
M34 x 1.5mm			







Rev 0 5/24 190



Pressure-activated, automatic shut-off vacuum assist nozzle for full-service and self-service stations.

Nozzle Options

Nozzle Guard Options



Waffle Guard Options

1808 Waffle Guard



TUV Vapor Insert


07329



Lever Options

Lever without Hold Open Clip

Lever with Hold Open Clip



Handguard Options

Standard Polymer Handguard (with or without Magnet) (with or without Magnet)



Latch Plate Options

1 - Position Latch Plate 2 - Position Latch Plate

Sightglass Option



Rev 0 5/24 191



Pressure-activated, automatic shut-off vacuum assist nozzle for full-service and self-service stations.

System Options

Safe-T-Breaks®

MODEL NO.	DESCRIPTION				
004034	Reconnectable Safe-T-Break®				
004034A*	Reconnectable Safe-T-Break® - Atex				
005134A*	Non-Reconnectable Safe-T-Break® - Atex				
006210	Non-Reconnectable Safe-T-Break®				
008332	MAGBREAK® Coax M34 CK				
010513	Non-Reconnectable Safe-T-Break® - Shearpin				

Spouts

MODEL NO. DESCRIPTION				
006291	V34 Spout Assy Kit (Includes 004000 VSG and 006391 Spout Assembly)			
006391	V34 Spout Assembly with Streamshaper®			

Pressure/Vacuum Vents

MODEL NO.	DESCRIPTION
004620	2" Slip-On Pressure Vacuum Vent
004885	2" Thread-On Pressure Vacuum Vent - NPT
005885	2" Thread-On Pressure Vacuum Vent with Internal Screen - NPT

Accessories, Testing and Maintenance

MODEL NO.	DESCRIPTION			
000397	Unleaded Spout Gauge			
003593	Hold Open Clip Kit			
004335	O-ring, Air / Liquid Test Spout Adaptor			
004360	Air / Liquid Spout Adaptor			
005233	O-ring Kit			
005260	Tool for dry Air / Liquid Test			
005837	Vapor Assist Flo-Equalizer®			
006941	Hose Conversion Adaptor M34 x 1.5			
007089	Nozzle Service Kit			

Swivels

MODEL NO.	DESCRIPTION		
004605	Multi-Plane Swivel		
004605A*	Multi-Plane Swivel - Atex		

Guards

MODEL NO.	DESCRIPTION
004231	Full Grip Reguard
006628	POPD® S Clear Cover
006660	POPD® S Full Grip Guard
006951	Full Grip Guard
007220	POPD® S Full Grip Reguard
007999	POPD® H Clear Cover
008184	POPD® H Full Grip Guard
008191	POPD® H Full Grip Reguard
010089	Black Handle Cover
014526	Mate Guard

Guard Color Chart

COLOR	SUFFIX	COLOR	SUFFIX	COLOR CUSTOM	SUFFIX
Blue	-01	Gold	-08	Amoco Blue	-07 сиѕтом
Red	-02	Silver	-09	Apple Green	-18 сиѕтом
Green	-03	■ BP Green	-16	Purple	-19 сиѕтом
Black	-04	M Blue	-25	Pink	-20 сиѕтом
Yellow	-05	Orange	-39	BPS Green	-22 сиѕтом
White	-06		·		•

Scuff Guards are to be ordered with the corresponding guard color option added to the model number. **Example:** If BLUE guards are desired, add guard color option -01 to the model number (159504-01). For custom colors, a minimum order of 4,000 guards will be required.



2325 Husky Way • Pacific, MO 63069 (800) 325-3558 • Fax (636) 825-7300 www.husky.com • sales@husky.com

